

UTILITIES & LANDSCAPES



LOAD  TRAIL

TV

TV03 Single Axle 4" Channel ATV Deckover 2,990 Lb GVWR

Stock photo. May be shown with additional options.



AVAILABLE SIZES

LENGTH	WEIGHT
96" X 14'	1,578 lbs.
*Base Weight Estimate Only	
Deck Height - 34"	



**17 COLORS
AVAILABLE**

STANDARD SPECIFICATIONS

**listed specs based on TV03 base model*

- 2,990 lb GVWR
- 3,500 lb GAWR (ea. axle)
- 4" Channel Tongue
- 4" Channel Frame
- 2" x 2" x 3/16" Angle, 16" OC Cross-members
- (1) 3,500 lb Dexter Idler/Spring Axle
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- Multi-Leaf Spring Suspension
- (1) 5,000 lb Top-wind Jack
- 2-5/16" Adjustable Coupler
- (2) - Safety Chains
- (4) U-Hooks
- Treated Pine Flooring
- Straight Deck w/5' Slide-In Ramps
- LED Lighting
- 16 Ga. 4-Way Double-Insulated Harness w/4-way Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black - Sherwin-Williams Powdura OneCure Primer w/Polyester TGIC Gloss Powder Topcoat

AXLE OPTIONS

(1) 3,500 Lb Dexter Elec/Spring (FSA)

COUPLER OPTIONS

2" Adjustable Coupler

GATES DOVETAILS, & RAMPS

5' Rear Slide-In Ramps

59" x 72" Snow Mobile Slide-In Ramps.

OTHER OPTIONS

Rough Oak Floor
 Douglas Fir Floor
 Blackwood Floor
 Steel DP Floor
 16" OC Cross-members
 7K Drop-Leg Jack
 Mud Flaps
 3" D-rings
 Tongue-Mount Tool Box
 Rub Rail
 Rear Support Stands (Tube or Jacks)
 Additional Stake Pockets
 Spare Tire & Mount
 Front Stone Guard

NOTES

Axles available in straight or torsion, with electric or hydraulic brakes.





SB03 | SB05
Single Axle 4" Channel Frame Utility
2,990 - 5,200 Lb GVWR

Stock photo. May be shown with additional options.



AVAILABLE SIZES

LENGTH	WEIGHT	LENGTH	WEIGHT
48" X 8'	782 lbs.	72" X 16'	1,508 lbs.
48" X 10'	851 lbs.	77" X 10'	1,101 lbs.
60" X 8'	871 lbs.	77" X 12'	1,260 lbs.
60" X 10'	967 lbs.	77" X 14'	1,371 lbs.
60" X 12'	1,070 lbs.	77" X 16'	1,547 lbs.
60" X 14'	1,227 lbs.	80" X 10'	1,383 lbs.
60" X 16'	1,361 lbs.	80" X 12'	1,462 lbs.
66" X 10'	1,041 lbs.	80" X 14'	1,603 lbs.
66" X 12'	1,144 lbs.	80" X 16'	1,760 lbs.
66" X 14'	1,301 lbs.	83" X 10'	1,250 lbs.
66" X 16'	1,435 lbs.	83" X 12'	1,329 lbs.
72" X 10'	1,114 lbs.	83" X 14'	1,470 lbs.
72" X 12'	1,217 lbs.	83" X 16'	1,627 lbs.
72" X 14'	1,374 lbs.		

**Base Weight Estimate Only
Deck Height - 21"*



FRONT FOLD-UP GATE AVAILABLE



17 COLORS AVAILABLE



SIDE RAIL RAMPS AVAILABLE

STANDARD SPECIFICATIONS

**listed specs based on SB03 base model*

- 2,990 lb GVWR
- 3,500 lb GAWR (ea. axle)
- 4" Channel Tongue
- 4" Channel Frame
- 2" x 2" x 3/16" Angle, 24" OC Cross-members
- (1) 3,500 lb Dexter Idler/Spring Axle
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- Multi-Leaf Spring Suspension
- (1) 5,000 lb Top-wind Jack
- 2" A-Frame Cast Coupler
- Straight Deck w/ Board Slides
- (2) - Safety Chains
- (4) U-Hooks
- Removable Smooth Plate Fenders
- Treated Pine Flooring
- 2" X 2" Sq Tube-Top Removable Side Rails
- LED Lighting
- 16 Ga. 4-Way Double-Insulated Harness w/4-way Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black - Sherwin-Williams Powdura OneCure Primer w/Polyester TGIC Gloss Powder Topcoat

AXLE OPTIONS

- (1) 3,500 Lb Dexter Elec/Spring (FSA)
- (1) 5,200 Lb Dexter Elec/Spring (FSA)
- (1) 3,500 Lb Dexter Elec/Drop(FSA)
- (1) 5,200 Lb Dexter Elec/Drop (FSA)
- (1) 3,500 Lb Dexter Elec/Torsion (FSA)
- (1) 5,200 Lb Dexter Elec/Torsion (FSA)

COUPLER OPTIONS

- 2-5/16" Adjustable Coupler
- 2" Adjustable Coupler

GATES DOVETAILS, & RAMPS

- 2' Dove Tail
- 3', 4' or 5' Fold-up Gate
- 3', 4', or 5' Split Fold-up Gate
- 3', 4', or 5' HD Fold-up Gate
- 3', 4', or 5' Fold-In Gate
- Front-Mount Fold-Up Gate
- Spring Assist For Gate(s)
- Side-Mount Gate
- Bi-Fold Gate
- Side Rail Ramps

OTHER OPTIONS

- ST225/75 R15 LRD Tires
- Rough Oak Floor
- Douglas Fir Floor
- Blackwood Floor
- Steel Diamond Plate Floor
- 16" OC Cross-members
- Steel Diamond Plate Fenders
- Aluminum Fenders
- 7K Drop-Leg Jack
- Tilt Deck
- 3" D-rings
- Angle Iron Side Rails (weld-on or removable)
- Pipe-top Side Rails (weld-on or removable)
- Sq. Tube Side Rails (weld-on or removable)
- Solid Metal Sides
- Expanded Metal Sides
- Tongue-Mount Tool Box
- Expanded Metal Tool Cage
- Rub Rail
- Rear Support Stands (Tube or Jacks)
- Stake Pockets
- Spare Tire & Mount

NOTES

Axles available in straight, drop or torsion, in idler or with electric or hydraulic brakes. Drop and Torsion axles available on 60", 77" & 80" wide models. Max deck width is 80" when drop axle option is selected. Length restrictions apply on dove tail options. Rub rail option not available with removable side rail option.

For a complete list of options available for this model, visit us at www.loadtrail.com



SE

SE03 Single Axle Angle Frame Landscape 2,990 Lb GVWR

Stock photo. May be shown with additional options.



AVAILABLE SIZES

LENGTH	WEIGHT	LENGTH	WEIGHT
48" X 8'	674 lbs.	72" X 10'	*
48" X 10'	746 lbs.	72" X 12'	*
60" X 8'	782 lbs.	72" X 14'	*
60" X 10'	872 lbs.	77" X 10'	990 lbs.
60" X 12'	968 lbs.	77" X 12'	1,103 lbs.
60" X 14'	1,102 lbs.	77" X 14'	1,254 lbs.

*Base Weight Estimate Only
Deck Height - 19"



**FRONT FOLD-UP GATE
AVAILABLE**



**17 COLORS
AVAILABLE**



**SIDE RAIL RAMPS
AVAILABLE**

STANDARD SPECIFICATIONS

**listed specs based on SE03 base model*

- 2,990 lb GVWR
- 3,500 lb GAWR (ea. axle)
- 3" Channel Tongue
- 2" x 3" x 3/16" Angle Frame
- 2" x 2" x 3/16" Angle, 24" OC Cross-members
- (1) 3,500 lb Dexter Idler/Spring Axle
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- Multi-Leaf Spring Suspension
- (1) 2,000 lb Top-wind Jack
- 2" A-Frame Coupler
- Straight Deck w/Board Slides
- (2) - Safety Chains
- (4) U-Hooks
- Weld-On Smooth Plate Fenders
- Treated Pine Flooring
- 2" X 2" Sq Tube-Top Weld-On Side Rails
- LED Lighting
- 16 Ga. 4-Way Double-Insulated Harness w/4-way Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black - Sherwin-Williams Powdura OneCure Primer w/Polyester TGIC Gloss Powder Topcoat

AXLE OPTIONS

(1) 3,500 Lb Dexter Elec/Spring (FSA)

OTHER OPTIONS

ST225/75 R15 LRD Tires
 Rough Oak Floor
 Douglas Fir Floor
 Blackwood Floor
 Steel Diamond Plate Floor
 16" OC Cross-members
 Steel Diamond Plate Fenders
 Aluminum Fenders
 5K Swivel Jack
 7K Drop-Leg Jack
 3" D-rings
 Angle Iron Side Rails
 Pipe-top Side Rails
 Sq. Tube Side Rails
 16" Solid Metal Sides
 16" Expanded Metal Sides
 Tongue-Mount Tool Box
 Expanded Metal Tool Cage
 Weed Eater Rack
 Rear Support Stands (Tube or Jacks)
 Stake Pockets
 Spare Tire & Mount (weld-on or removable)

NOTES

Axles available with electric or hydraulic brakes. Length restrictions apply on dove tail options.

COUPLER OPTIONS

2" Adjustable Coupler
2" Cast A-Frame Coupler

GATES DOVETAILS, & RAMPS

2' Dove Tail
 3', 4' or 5' Fold-up Gate
 3', 4', or 5' Split Fold-up Gate
 3', 4', or 5' HD Fold-up Gate
 3', 4', or 5' Fold-In Gate
 Bi-Fold Gate
 Front-Mount Fold-Up Gate
 Side-Mount Gate
 Spring Assist For Gate(s)
 Side Rail Ramps

For a complete list of options available for this model, visit us at www.loadtrail.com



LS

LS03 | LS05 Single Axle 4" Channel Frame Landscape 2,990 - 5,200 Lb GVWR



Stock photo. May be shown with additional options.

AVAILABLE SIZES

LENGTH	WEIGHT	LENGTH	WEIGHT
48" X 8'	955 lbs.	77" X 16'	1,816 lbs.
48" X 10'	1,037 lbs.	80" X 10'	1,498 lbs.
60" X 8'	1,028 lbs.	80" X 12'	1,695 lbs.
60" X 10'	1,148 lbs.	80" X 14'	1,859 lbs.
60" X 12'	1,304 lbs.	80" X 16'	2,005 lbs.
60" X 14'	1,440 lbs.	83" X 10'	1,365 lbs.
60" X 16'	1,586 lbs.	83" X 12'	1,562 lbs.
77" X 10'	1,313 lbs.	83" X 14'	1,726 lbs.
77" X 12'	1,483 lbs.	83" X 16'	1,872 lbs.
77" X 14'	1,638 lbs.		

**Base Weight Estimate Only
Deck Height - 21"*



**FRONT TOOL CAGE
AVAILABLE**



**17 COLORS
AVAILABLE**



**WEED EATER RACK
AVAILABLE**

STANDARD SPECIFICATIONS

**listed specs based on LS03 base model*

- 2,990 lb GVWR
- 3,500 lb GAWR (ea. axle)
- 4" Channel Tongue
- 4" Channel Frame
- 2" x 2" x 3/16" Angle 24" OC Cross-members
- (1) 3,500 lb Dexter Idler/Spring Axle
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- Multi-Leaf Spring Suspension
- (1) 5,000 lb Top-wind Jack
- 2" Cast A-Frame Coupler
- (2) - Safety Chains
- Removable Smooth Plate Fenders
- 2' Removable Expanded Metal Side Rails
- 4' Fold-Up Gate w/Tubing
- Treated Pine Flooring
- LED Lighting
- 16 Ga. 4-Way Double-Insulated Harness w/4-way Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black - Sherwin-Williams Powdura OneCure Primer w/ Polyester TGIC Gloss Powder Topcoat

AXLE OPTIONS

- (1) 3,500 Lb Dexter Elec/Spring (FSA)
- (1) 5,200 Lb Dexter Elec/Spring (FSA)

COUPLER OPTIONS

- 2-5/16" Adjustable Coupler
- 2" Adjustable Coupler
- 3" Adjustable Pintle Ring

GATES DOVETAILS, & RAMPS

- 2' Dove Tail
- 3', 4', or 5' Split Fold-up Gate
- 3', 4', or 5' HD Fold-up Gate
- 3', 4', or 5' Fold-In Gate
- Front-Mount Fold-Up Gate
- Bi-Fold Gate
- Side-Mount Gate
- Spring Assist For Gate

OTHER OPTIONS

- ST225/75 R15 LRD Tires
- Rough Oak Floor
- Douglas Fir Floor
- Blackwood Floor
- Steel DP Floor
- 16" OC Cross-members
- Steel Diamond Plate Fenders
- Aluminum Fenders
- 7K Drop-Leg Jack
- 3" D-rings
- Angle Iron Side Rails (weld-on or removable)
- Pipe-top Side Rails (weld-on or removable)
- Sq. Tube Side Rails (weld-on or removable)
- 24" Solid Metal Sides
- 36" Solid Metal Sides
- 48" Solid Metal Sides
- 36" Expanded Metal Sides
- 48" Expanded Metal Sides
- Running Boards
- Tongue-Mount Tool Box
- Expanded Metal Tool Cage
- Weed Eater Rack
- Rear Support Stands (Tube or Jacks)
- Stake Pockets
- Spare Tire & Mount (weld-on or removable)

NOTES

Axles available with electric or hydraulic brakes.

For a complete list of options available for this model, visit us at www.loadtrail.com



TV

TV07 Single Axle 4" Channel ATV Deckover 7,000 Lb GVWR

Stock photo. May be shown with additional options.



AVAILABLE SIZES

LENGTH	WEIGHT
96" X 16'	2,238 lbs.
96" X 23'	2,801 lbs.
*Base Weight Estimate Only	
Deck Height - 34"	



**17 COLORS
AVAILABLE**

STANDARD SPECIFICATIONS

**listed specs based on TV07 base model*

- 2,990 lb GVWR
- 3,500 lb GAWR (ea. axle)
- 4" Channel Tongue
- 4" Channel Frame
- 2" x 2" x 3/16" Angle, 16" OC Cross-members
- (2) 3,500 lb Dexter 1 Elec Spring Axle
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- Multi-Leaf Spring Suspension
- (1) 5,000 lb Top-wind Jack
- 2-5/16" Adjustable Coupler
- (2) - Safety Chains
- Treated Pine Flooring
- Straight Deck w/5' Slide-In Ramps
- LED Lighting
- 16 Ga. 5-Way Double-Insulated Harness w/7-way Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black - Sherwin-Williams Powdura OneCure Primer w/Polyester TGIC Gloss Powder Topcoat

AXLE OPTIONS

(2) 3,500 Lb Dexter Elec/Spring (FSA)

COUPLER OPTIONS

2-5/16" Adjustable Coupler

2" Adjustable Coupler

GATES DOVETAILS, & RAMPS

5' Rear Slide-In Ramps

59" x 72" Snow Mobile Slide-In Ramps.

OTHER OPTIONS

Rough Oak Floor
 Douglas Fir Floor
 Blackwood Floor
 Steel Diamond Plate Floor
 16" OC Cross-members
 7K Drop-Leg Jack
 Mud Flaps
 3" D-rings
 Tongue-Mount Tool Box
 Rub Rail
 Rear Support Stands (Tube or Jacks)
 Stake Pockets
 Spare Tire & Mount
 Front Stone Guard

NOTES

Axles available in straight or torsion, with electric or hydraulic brakes.

For a complete list of options available for this model, visit us at www.loadtrail.com



UT

UT07 Tandem Axle 4" Channel Utility 7,000 Lb GVWR

Stock photo. May be shown with additional options.



AVAILABLE SIZES

LENGTH	WEIGHT	LENGTH	WEIGHT
60" X 10'	1,198 lbs.	83" X 12'	1,544 lbs.
60" X 12'	1,311 lbs.	83" X 14'	1,676 lbs.
60" X 14'	1,418 lbs.	83" X 16'	1,823 lbs.
60" X 16'	1,525 lbs.	83" X 18'	1,965 lbs.
60" X 18'	1,632 lbs.	83" X 20'	2,110 lbs.
60" X 20'	1,739 lbs.	102" X 10'	1,672 lbs.
77" X 10'	1,406 lbs.	102" X 12'	1,812 lbs.
77" X 12'	1,477 lbs.	102" X 14'	1,952 lbs.
77" X 14'	1,599 lbs.	102" X 16'	2,092 lbs.
77" X 16'	1,740 lbs.	102" X 18'	2,232 lbs.
77" X 18'	1,873 lbs.	102" X 20'	2,380 lbs.
77" X 20'	2,009 lbs.	102" X 22'	2,496 lbs.
83" X 10'	1,405 lbs.		

**[Base Weight Estimate Only]
Deck Height - 21"*



**BI-FOLD GATE
AVAILABLE**



**17 COLORS
AVAILABLE**



**SIDE RAIL RAMP
AVAILABLE**

STANDARD SPECIFICATIONS

**listed specs based on UT07 base model*

- 7,000 lb GVWR
- 3,500 lb GAWR (ea. axle)
- 4" Channel Tongue
- 4" Channel Frame
- 2" x 2" x 3/16" Angle, 24" OC Cross-members
- (2) 3,500 lb Dexter 1 Elec/Spring Axles
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- Multi-Leaf Spring Suspension
- (1) 5,000 lb Top-wind Jack
- 2" Cast A-Frame Coupler
- Straight Deck w/ Board Slides
- (2) - Safety Chains
- Square Tube-Top Weld-On Side Rails
- Weld-On Smooth Plate Tear-Drop Fenders
- (4) U-Hooks
- Treated Pine Flooring
- LED Lighting
- 16 Ga. 5-Way Double-Insulated Harness w/7-way Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black - Sherwin-Williams Powdura OneCure Primer w/Polyester TGIC Gloss Powder Topcoat

AXLE OPTIONS

- (2) 3,500 Lb Dexter Elec/Spring (FSA)
- (2) 3,500 Lb Dexter Elec/Drop (FSA)
- (2) 3,500 Lb Dexter Elec/Torsion (FSA)

COUPLER OPTIONS

- 2" Adjustable Coupler
- 2-5/16" Adjustable Coupler

GATES DOVETAILS, & RAMPS

- 2' Dove Tail
- 3', 4' or 5' Fold-up Gate
- 3', 4', or 5' Split Fold-up Gate
- 3', 4', or 5' HD Fold-up Gate
- 3', 4', or 5' Fold-In Gate
- Front-Mount Fold-Up Gate
- Spring Assist For Gate(s)
- Side Rail Ramps
- 5' x 13" Slide-In Ramps
- Bi-Fold Gate
- Side-Mount Gate

OTHER OPTIONS

- ST225/75 R15 LRD Tires
- Rough Oak Floor
- Douglas Fir Floor
- Blackwood Floor
- Steel Diamond Plate Floor
- 16" OC Cross-members
- Steel Diamond Plate Fenders
- Aluminum Fenders
- 7K Drop-Leg Jack
- 3" D-rings
- Angle Iron Side Rails (weld-on or removable)
- Pipe-top Side Rails (weld-on or removable)
- Sq. Tube Side Rails (weld-on or removable)
- 16" Solid Metal Sides
- 16" Expanded Metal Sides
- Tongue-Mount Tool Box
- Expanded Metal Tool Cage
- Weed Eater Rack
- Rear Support Stands (Tube or Jacks)
- Stake Pockets
- Spare Tire & Mount (weld-on or removable)

NOTES

Axles available in straight, drop or torsion with electric or hydraulic brakes. Torsion & Drop axle options available on 60", 77" & 80" models only. 2 ft. dove tail option available only on 12+ deck length models & up.

For a complete list of options available for this model, visit us at www.loadtrail.com



UE

UE07 Tandem Axle Angle Utility 7,000 Lb GVWR

Stock photo. May be shown with additional options.



AVAILABLE SIZES

LENGTH	WEIGHT
60" X 10'	1,045 lbs.
60" X 12'	1,158 lbs.
60" X 14'	1,265 lbs.
60" X 16'	1,373 lbs.
77" X 10'	1,253 lbs.
77" X 12'	1,324 lbs.
77" X 14'	1,446 lbs.
77" X 16'	1,587 lbs.
83" X 10'	1,252 lbs.
83" X 12'	1,391 lbs.
83" X 14'	1,523 lbs.
83" X 16'	1,670 lbs.
83" X 18'	1,812 lbs.
<i>*Base Weight Estimate Only</i>	
Deck Height - 19"	



**17 COLORS
AVAILABLE**

STANDARD SPECIFICATIONS

**listed specs based on UE07 base model*

- 7,000 lb GVWR
- 3,500 lb GAWR (ea. axle)
- 4" Channel Tongue
- 2" x 3" x 3/16" Angle Frame
- 2" x 3" x 3/16" Angle 24" OC Cross-members
- (2) 3,500 lb Dexter 1 Elec/Spring Axles
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- Multi-Leaf Spring Suspension
- (1) 2,000 lb Top-wind Jack
- 2" Cast A-Frame Coupler
- (2) - Safety Chains
- Sq Tube Weld-on Side Rails, 2" x 2" x 3/16"
- 2" x 2" x 1/8" Rail Uprights
- Weld-on Smooth Plate Fenders
- Treated Pine Flooring
- LED Lighting
- 16 Ga. 5-Way Double-Insulated Harness w/ 7-way Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black - Sherwin-Williams Powdura OneCure Primer w/ Polyester TGIC Gloss Powder Topcoat

AXLE OPTIONS

(2) 3,500 Lb Dexter Elec/Spring (FSA)

COUPLER OPTIONS

2" Adjustable Coupler
2-5/16" Adjustable Coupler
2-5/16" A-frame Coupler

GATES DOVETAILS, & RAMPS

2' Dove Tail
3', 4', or 5' Fold-up Gate
3', 4', or 5' Split Fold-up Gate
3', 4', or 5' HD Fold-up Gate
3', 4', or 5' Fold-In Gate
Front-Mount Fold-Up Gate
Spring Assist For Gate(s)
Side Rail Ramps
5' x 13" Slide-In Ramps
Bi-Fold Gate
Side-Mount Gate

OTHER OPTIONS

ST225/75 R15 LRD Tires
Rough Oak Floor
Douglas Fir Floor
Blackwood Floor
Steel Diamond Plate Floor
12" or 16" OC Cross-members
Steel Diamond Plate Fenders
Smooth Plate Fenders
5K Swivel Jack
7K Drop-Leg Jack
3" D-rings
Angle Iron Side Rails (weld-on)
Pipe-top Side Rails (weld-on)
Sq. Tube Side Rails (weld-on)
Solid Form Sides
16" Solid Metal Sides
16" Expanded Metal Sides
Tongue-Mount Tool Box
Expanded Metal Tool Cage
Weed Eater Rack
Rear Support Stands (Tube or 5K Jacks)

OTHER OPTIONS

Stake Pockets
Spare Tire & Mount (weld-on or removable)

NOTES

Axles available with electric or hydraulic brakes.
2' dove tail available on 12 ft. & Up models only.

For a complete list of options available for this model, visit us at www.loadtrail.com



LT

LT07 Tandem Axle 4" Channel Landscape Trailer | 7,000 Lb GVWR

Stock photo. May be shown with additional options.



AVAILABLE SIZES

LENGTH	WEIGHT	LENGTH	WEIGHT
60" X 10'	1,415 lbs.	80" X 14'	1,926 lbs.
60" X 12'	1,559 lbs.	80" X 16'	2,082 lbs.
60" X 14'	1,677 lbs.	80" X 18'	2,212 lbs.
77" X 10'	1,611 lbs.	80" X 20'	2,402 lbs.
77" X 12'	1,762 lbs.	83" X 10'	1,687 lbs.
77" X 14'	1,896 lbs.	83" X 12'	1,822 lbs.
77" X 16'	2,050 lbs.	83" X 14'	1,985 lbs.
77" X 18'	2,200 lbs.	83" X 16'	2,141 lbs.
77" X 20'	2,351 lbs.	83" X 18'	2,271 lbs.
80" X 10'	1,628 lbs.	83" X 20'	2,461 lbs.
80" X 12'	1,763 lbs.		

*Base Weight Estimate Only
Deck Height - 21"



**FRONT TOOL CAGE
AVAILABLE**



**17 COLORS
AVAILABLE**



**WEED EATER RACK
AVAILABLE**

STANDARD SPECIFICATIONS

- 7,000 lb GVWR
- 3,500 lb GAWR (ea. axle)
- 4" Channel Tongue
- 4" Channel Frame
- 2" x 2" x 3/16" Angle, 24" OC Cross-members
- (2) 3,500 lb Dexter 1 Elec/Spring Axle
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- Multi-Leaf Spring Suspension
- (1) 5,000 lb Top-wind Jack
- 2" Cast A-Frame Coupler
- (2) - Safety Chains
- Smooth Plate Removable Tear-Drop Fenders
- 2' Sq. Tube-Top Expanded Metal Removable Side Rails
- 2" x 2" x 1/8" Tube Uprights
- 4' Fold-Up Gate
- Treated Pine Flooring
- LED Lighting
- 16 Ga. 5-Way Double-Insulated Harness w/7-way Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black - Sherwin-Williams Powdura OneCure Primer w/Polyester TGIC Gloss Powder Topcoat

AXLE OPTIONS

- (2) 3,500 Lb Dexter Elec/Spring (FSA)
- (2) 3,500 Lb Dexter Elec/Drop (FSA)
- (2) 3,500 Lb Dexter Elec/Torsion (FSA)

COUPLER OPTIONS

- 2" Adjustable Coupler
- 2-5/16" Adjustable Coupler
- 2-5/16" A-frame

GATES DOVETAILS, & RAMPS

- 2' Dove Tail
- 3', 4' or 5' Fold-up Gate
- 3', 4', or 5' Split Fold-up Gate
- 3', 4', or 5' HD Fold-up Gate
- 3', 4', or 5' Fold-In Gate
- Front-Mount Fold-Up Gate
- Spring Assist For Gate(s)
- Side Rail Ramps
- 5' x 13" Slide-In Ramps
- Bi-Fold Gate
- Side-Mount Gate

OTHER OPTIONS

- ST225/75 R15 LRD Tires
- Rough Oak Floor
- Douglas Fir Floor
- Blackwood FLOOR
- Steel Diamond Plate Floor
- 16" OC Cross-members
- Steel Diamond Plate Fenders
- Aluminum Fenders
- 5K Swivel Jack
- 7K Drop-Leg Jack
- Additional 3" D-rings
- Angle Iron Side Rails (weld-on or removable)
- Pipe-top Side Rails (weld-on or removable)
- Sq. Tube Side Rails (weld-on or removable)
- 24" Solid Metal Sides
- 36" Solid Metal Sides
- 48" Solid Metal Sides
- 36" Expanded Metal Sides
- 48" Expanded Metal Sides
- Running Boards
- Tongue-Mount Tool Box
- Expanded Metal Tool Cage
- Weed Eater Rack

OTHER OPTIONS

- Rear Support Stands (Tube or Jacks)
- Additional Stake Pockets
- Spare Tire & Mount (weld-on or removable)

NOTES

Axles available in straight, drop or torsion with electric or hydraulic brakes.

For a complete list of options available for this model, visit us at www.loadtrail.com



POPULAR OPTIONS



Running Boards



Front Fold-Up Gate



Blackwood Lumber Decking



Tongue-mount Tool Box



Front Tool Cage



Weed-Eater Rack



4' Fold-Up Gate



Side Rail Ramps



Pipe-Top Side Rails

KEY ADVANTAGES

- Industry Best Warranty
- Roadside Assistance
- National Dealer Network
- Commercial Grade Construction
- Dexter E-Z Lube Axles
- Dexter Nev-R Adjust™ Forward Self Adjusting Electric Brake Axles
- Sherwin Williams® Powder Coat
- Primer Standard
- Fully Coated Under Trailer
- Radial Tires Standard
- Powder Coated Wheels
- Channel Wrapped Tongue *Length Restrictions Apply
- Fully Coated Under Trailer
- Channel & Angle Frame Construction
- 24" On-Center Cross-members
- Tie-Downs
- Pressure Treated 2x6 Decking
- Recessed DOT Compliant LED Lighting
- Premium Fully Sealed Wiring Harness w/Polar Cord
- NATM Compliant
- Sandblasted and Zirconium Washed
- Hand Pinstriping
- Innovative Design
- Endless Options for Customization
- Made in USA

